

Version	2.0	Date	9/17/2018
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Wall Pack
Item Number	7777
Stock Code	LED-FXTWP55/40K/DB
Mounting	Wall Mount
Housing Color	Dark Bronze



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	58	Replacement Wattage (W)	400
Tested Wattage (W)	58.26		
Input Voltage (V)	120-277V	Surge Protect Level	2KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.48	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	8,382	CCT (K)	4000K
Efficacy (lm/w)	144	Beam Angle (°)	Forward Throw
CRI	70		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-22°F ~ 131°F
Storage Temperature (°F)	-22°F ~ 140°F
IP Rating	IP65
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
7334	BAEM15-48BC/MV-A	15W CEC Compliant LED Emergency Driver
P10234	SEN-MC605V-D	Microwave Motion Sensor
P10036	SEN-PHO-BT-MT/MV	Photocell

PRODUCT DIMENSIONS		
Width- in / (mm)	14.5" / 363	
Height- in / (mm)	9" / 230	
Depth- in / (mm)	7.5" / 188	
EPA (ft²)	-	
Weight (lbs)	7	
Mounting Height (ft)	-	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC		RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS